



TOUCH MONITOR



MONITOR



OPEN FRAME



TOUCH SCREEN



DIGITAL SIGNAGE



TOUCH TABLE



FLOOR STANDING



VIDEOWALL

www.worldtradedisplay.com

DISPLAY DIGITAL SOLUTIONS

Touch Sanitizer Gel Dispenser/ Thermal Temp. Scan/ Face Mask Recognize



Display & Digital Signage Solutions

Detect the Temperature

Automatic facial recognition system and body temperature scan non-contact from + 28° to 43 ° with precision +/- 0.1 ° C.

Check Mask

The important automatic facial recognition via camera to identify if the mask is worn or not and to be able to get-in.

"NOTICE" Touch Monitor

21.5' inch capacitive touch screen monitor for displaying the "STOP WARNING" screen. Possibility of customizing screens.

Benefits

We present our innovative thermo-scanner for temperature detection, which promotes safety in all public and private companies. It can also be positioned with different type of stands in shops and structures, such as airports, stations, subways that register a significant influx of people every day.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Digital Signage
	Panel Size available	21.5"
	Active Area Aspect Ratio Resolution	21.5" 477 x 268 mm 16:9 1920 x 1080
	Brightness	300 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	5 ms
	Contrast Ratio	1000:1
	Input Video Format	RGB Analog/ DVI-D /HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
	Double Display	No
	PC Functions	CPU
RAM		2 Gb
SSD		8 Gb
Connections		3G/4G/WIFI/Bluetooth
Media Player		Yes
System OS		-
Android		Version 7.1 English (Default) - Multi-language
Peripheral Ports		2 Host USB (Built-in), 1 RJ45, 1 Line Out, 1 Mic Int, 1 HDMI, 1 VGA
Other Function		On Request
Touch Functions	Technology	PCAP
	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<15 ms
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	Built- in speaker 8 Ohm/ 5 watt *2 pcs
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: -10° ~ 50°C Storage: -15° ~ 50°C
	Screen Position	Vertical
	Camera	Dual-Hens Camera HDR2MP
	Face Recognition Height	1.2-2.2m
	Face Recognition Distance	0.5-3m
	Face Recognition Time	< 0.5s
Mechanical	Installation (VESA)	Wallmount - Floor Standing Base (optional)
	Sheel Material	Aluminium alloy
	Glass	Tempered Glass
	Enclosure Color	White Color (standard) - Customized colors based on MOQ
Power & Accessory	Power Supply	DC 12V/3A
	Power Cons. (Max)	35 W

FEATURES	REMARKS	SPECIFICATIONS
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko
Sanitizer Dispensing	Dispensing Sanitizer	Auto dispense of Sanitizer with hand motion
	Sanitizer Capacity	1000 ml capacity of Sanitizer Content
	Indicator	Light indicator when consume over 75% of sanitizer
Packaging	Dimension (Net) (L X W X H) Weight (Single)	21.5" 450 x 350 x 1775 mm 14 kg
	Carton Dimension (L X W X H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Auto Dispenser	<ol style="list-style-type: none"> 1. Auto Dispense: Auto Dispense by Sensor, touch free to avoid cross infection; 2. Auto Identify: Identify the disinfectant automatically, only work for the authorized one;(Optional) 3. Dispensing Life: The life of our dispenser is more than 650000 times; Each drop is about 2ML for Liquid.
	Face recognition	<ol style="list-style-type: none"> 1. Support face recognition and comparison while wearing a mask. 2. Using industrial-grade binocular wide dynamic camera.
	Body Temp. Measurement	<ol style="list-style-type: none"> 1. Support human body temperature detection, temperature display. 2. 0.5-0.8 meter ultra-distant body temperature detection, 0.3 error. 3. Support and automatic alarm for abnormal body temperature.
	Accessories	Remote Control, Keys, Wallmount bracket, Screws, Power Cable, WiFi Antenna
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.