



[www.worldtradedisplay.com](http://www.worldtradedisplay.com)

## MONITOR

### Monitor Solutions – TOP Wallmount Series



Display & Digital Signage Solutions

#### Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

#### All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

#### Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

#### Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Monitor
	Panel Size available	32"
	Active Area	32" 698 x 393 mm
	Aspect Ratio	16:9
	Resolution	1920 x 1080
	Brightness	450 cd/m2
	Colors	16.7 million
	Viewing Angle	Horizontal (left/right): 178°/ Vertical (up/down): 178°
	Response Time (Pixel)	8 ms
	Contrast Ratio	5000:1
	Input Video Format	RGB Analog/ DVI Digital
	Input Video Signal	VGA/ DVI-D
	Input Frequency	Horizontal: 30 - 82 kHz Vertical: 60 - 75 Hz
	OSD	-
	High Brightness	No
High 4K Resolution	No	
Double Display	No	
PC Functions	CPU	-
	RAM	-
	SSD	-
	Connections	-
	Media Player	-
	System OS	-
	Android	-
	OPS Module Slot	-
	Other Function	-
Touch Functions	Technology	-
	Point	-
	Interface	-
	Surface Hardness	-
	Resolution	-
	Response Time	-
	Input Method	-
Connectivity	Interface	VGA, DVI-DI
	Speaker	-
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 60°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	100 x 100 Side
	Sheel Material	Aluminium frame and body
	Glass	-
	Enclosure Color	Metal Gray

FEATURES	REMARKS	SPECIFICATIONS
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	40W
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko
Packaging	Dimension (Net) (L x W x H) Weight (Single)	32" 760 x 110 x 450 mm 9.7 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	-
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.