















www.worldtradedisplay.com

DIGITAL SIGNAGE SOLUTIONS (AiO)

PCAP All in One Touch Solutions - ABA Wallmount Series



Display & Digital Signage Solutions

Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.



marketing@worldtradedisplay.com



TECHNICAL SPECIFICATION

DIGITAL SIGNAGE | PCAP ABA SERIES

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Digital Signage
	Panel Size available	13.3"/ 15.1"
	Active Area Aspect Ratio Resolution	13.3" 295 x 167 mm 16:9 1920 x 1080 15.1" 305 x 229 mm 4:3 1024 x 768
	Brightness	250 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 170° Vertical (up/down): 160°
	Response Time (Pixel)	5 ms
	Contrast Ratio	1000:1
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
	Double Display	No
PC Functions	CPU	Celeron C3855
	RAM	4/ 8/ 16 Gb
	SSD	64/ 128/ 256 Gb
	Connections	Wi-Fi x1, RJ45 x1
	Media Player	Yes
	System OS	Windows/ Linux/ Other
	Android	-
	OPS Module Slot	No
	Other Function	On Request
Touch Functions	Technology	PCAP
Todell'i dilettoris	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<15
	Input Method	
C	/	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range Screen Position	Operating: 0° ~ 50°C Storage: -20° ~ 70°C
Mechanical	Installation (VESA)	Landscape (Default) or Portrait 75 x75 Side/ 75 x 100 Side/ 100 x 100 Side/
Wechanical	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Silver Frame and Black Body
Dower S Assessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
Power & Accessory		·
	Power Cons. (Max)	Max: 25W
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko



TECHNICAL SPECIFICATION

TOUCH MONITOR | PCAP ABA SERIES

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H) Weight (Single)	13.3" 350 x 34 x 222 mm 3.6 Kg 15.1" 349 x 207 x 353 mm 4.2 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.

