



TOUCH MONITOR



MONITOR



OPEN FRAME



TOUCH SCREEN



DIGITAL SIGNAGE



TOUCH TABLE



FLOOR STANDING



VIDEO WALL

[www.worldtradedisplay.com](http://www.worldtradedisplay.com)

## SELF-SERVICE KIOSK

### Self-Service Kiosk Solutions – CITY Standing Series



Display & Digital Signage Solutions

#### Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

#### All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

#### Common Scenarios

Innovative & communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

#### Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Self-Service Kiosk
	Panel Size available	21.5"
	Active Area	21.5" 476 x 268 mm
	Aspect Ratio	16:9
	Resolution	1920 x 1080
	Brightness	250 cd/m <sup>2</sup>
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	8 ms
	Contrast Ratio	700:1
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
Double Display	No	
PC Functions	CPU	Atom/ i3
	RAM	2 Gb
	HDD	500 Gb
	Connections	Wi-Fi x1, RJ45 x1
	Media Player	Yes
	System OS	Windows
	Android	-
	OPS Module Slot	No
	Other Function	On Request
Touch Functions	Technology	I.R. Infrared
	Point	2
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	5 <10 ms
	Input Method	Finger or any pointer minimum radius 3 mm
Connectivity	Interface	USB
	Speaker	2-10W Built in Stereo
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 50°C Storage: -20° ~ 70°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	Metal Base
	Sheet Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Black and Grey
Power & Accessory	Power Supply	AC 110-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	45 W
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H)	21.5" 602 x 425 x 1461 25 Kg
	Weight (Single)	
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
		Special mechanical design/ style guarantee overtime
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.