



ADVERTISING PLAYER

With 25 years of experience in the information technology sector and sales in over 32 countries worldwide, World Trade Display has all the necessary resources to ensure the realization of digital projects of any size to allow companies to compete in their own market reference.

The offer includes the design and direct supply of displays in different interpretations, as well as the possibility of carrying out custom projects with specific requests on any digital asset; starting from the normal open frame monitors only visualization in industrial version to get to the most engaging interactive displays in different and multiple technologies; moving from the most complex videowalls to reach the advertising floor standing players, the latter increasingly widespread in the public spaces of the various merchandising sectors today, with a guaranteed technical coverage and an absolutely innovative design.

The World Trade Display mission is to offer the tools and an overview to create revolutionary interactive ideas that make companies more competitive, in all those sectors such as Vending, Gaming, Digital Signage or others, with different solutions by Touch Monitor, Open Frame, Touch Screen, Digital Signage Display, Interactive Table, Advertising Player, Self-Service Kiosk and Videowall.







OPEN FRAME



TOUCH SCRFFN



DISPLAY DIGITAL SIGNAGE



INTERACTIVE TABLE



ADVERTISING PLAYER



SELE SERVICE KIOSK



VIDEOWALL



DEVICE



TOUCH FLOOR STANDING | I.R.

BIC SERIES

MODEL	FSLIB-4904-34S128	FSLIB-5504-34S128	
NEDI AV			
DISPLAY			
Display Size	49" Inch	55" Inch	
Active Display Area (H x V)	1039,68 x 584,82 mm	1203 x 680 mm	
Aspect Ratio	16:9	16:9	
Type Version	Touch Floor Standing	Touch Floor Standing	
LCD Technology	Active Matrix TFT LCD	Active Matrix TFT LCD	
Native Resolution	1080x1921	1080x1920	
Colors	16,7 million	16,7 million	
Brightness	1500 cd/m2	500 cd/m2	
Response Time (Pixel)	6 ms	6 ms	
Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178		
Contrast Ratio	4000:1	4000:1	
Input Video Format	RGB Analog/HDMI	RGB Analog/HDMI	
Input Video Signal	VGA/HDMI	VGA/HDMI	
Input Frequency			
High 4K Resolution	On Demand	On Demand	
High Brightness	On Demand	On Demand	
Double Display	No	No	
PC FUNCTIONS			
CPU	i3 (Call us for different Configuration)	i3 (Call us for different Configuration)	
Memory RAM	4 Gb (Call us for different Configuration)	4 Gb (Call us for different Configuration)	
Storage (HDD/SSD)	128 Gb SSD (Call us for different Configuration)	128 Gb SSD (Call us for different Configuration)	
Operative System	Windows - Linux	Windows - Linux	
Media Player	No	No	
Android	On Demand	On Demand	
OPS Module Slot			
Motherboards			
TOUCH FUNCTIONS			
Technology	I.R. Infrared	I.R. Infrared	
Point	6	6	
Interface	USB	USB	
	036	038	
Surface Hardness			
Resolution			Y
Response Time			
Input Method	Finger, pen or other	Finger, pen or other	
On Item Reques			
Type Controller			
CONNECTIVITY			
Interface	USB	USB	
Speaker	2-5W Built in Stereo	2-5W Built in Stereo	
FUNCTION CONDITIONS	2 3W Built III Stereo	E 5W Built III Stereo	
	One-anti-net 2007 (2007 Standard 10.07 (2007	Oti200/ 000/ 5t10.0/ 000/	
Relative Humidity	Operating: 20% - 80% Storage: 10 % - 90%	Operating: 20% - 80% Storage: 10 % - 90%	
Temperature Range	Operating: 0° - 50°C Storage: -20° - 70°C	Operating: 0° - 50°C Storage: -20° - 70°C	
Screen Position	Portrait (Default) or Landscape	Portrait (Default) or Landscape	
MECHANICAL SPECIFICATIONS			
Sheel Material	Alluminium Frame	Alluminium Frame	
Glass	Anti-glare Tempered Glass	Anti-glare Tempered Glass	
Enclosure Color	Silver Frame and Black Body	Silver Frame and Black Body	
Mounting (Option)			
POWER & ACCESSORY			
Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz	AC 100-240V Input DC 12V, 24V 50/60 Hz	
		·	
Power Consumption (Max)	180 W	195 W	
Cables	Power Supply with Cable Schuko	Power Supply with Cable Schuko	
Input Connector	AC: Cable Power Schuko	AC: Cable Power Schuko	
PACKAGING			
Dimension (Net)	1850x707x460 mm	1916x806x500 mm	
Multibox Carton Dimension	1923x815x250 mm	2240x1110x300 mm	
Q.ty Multibox	1	1	
Weight (Single) (Appr.)	90 Kg	110 Kg	
POLICY			
Warranty	2 Years (Panel 1 Year)	2 Years (Panel 1 Year)	
Agency Approval	CE - FCC - CCC	CE - FCC - CCC	
OTHER FEATURES/ UPGRADE			
Extra Time Warranty	Please contact us if you need more		
Different Version Technolgy	Available also in Android Version		
	Available also with 4K, High Brightness and other kind od panel		
	Available also with many different colors on demand		
	Available also with different desk/base		
Shell Material		Printer Webcam Coin Acceptor	
	Available also with Barcode Reader, ID Card; IC Card; Printer, Webcam, Coin Acceptor Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.		
Notes	raniei specification above comes from typical panel a	and for reference only, please contact our sales for the final confir	mation, il needed.

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World and Design and Control Production of the Control Prod