



[www.worldtradedisplay.com](http://www.worldtradedisplay.com)

## DIGITAL SIGNAGE SOLUTIONS (AiO)

### I.R. All in One Touch Solutions - BETA Wallmount Series



**Display & Digital Signage Solutions**

#### Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

#### All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

#### Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

#### Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Digital Signage
	Panel Size available	21.5"/ 49"
	Active Area	21.5" 477 x 268 mm 16:9 1920 x 1080
	Aspect Ratio	49" 1013 x 633 mm 16:9 1920 x 1080
	Resolution	
	Brightness	250/ 360 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	25/ 14 ms
	Contrast Ratio	1000:1/ 1400:1 (Range)
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
Double Display	No	
PC Functions	CPU	Atom/ i3
	RAM	2Gb/ 4Gb
	SSD	320 Gb/ 500 Gb
	Connections	Wi-Fi x1, RJ45 x1
	Media Player	Yes
	System OS	Windows/ Linux/ Other
	Android	-
	OPS Module Slot	No
Other Function	On Request	
Touch Functions	Technology	infrared Touch (IR)
	Point	6
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<5 ms
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	5W x 2
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 65°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	75 x75 Side/ 75 x 100 Side/ 100 x 100 Side/
	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Silver Frame and Black Body/ 49" inch: Gold version
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	Max: 65W
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H)	21.5" 545 x 45 x 337 7.2 Kg
	Weight (Single)	49" 1124 x 65 x 654 18.3 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
		Special mechanical design/ style guarantee overtime
		Slim design to fit your kiosk easy way
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.