WTD ™
WORLD TRADE DISPLAY

LED WALL SOLUTIONS

Portable Car LED CART Series
Lift and Foldable All-in-one

worldtradedisplay.com

Your choice to
discover the
technologies

Wide range
of innovative
digital products

Increase your
growth and
company profit

LED WALL SOLUTIONS

CART Series Lift and Foldable All-in-one Version

	Display Size	115,6"	136"	163"	220"
Screen Parameter	Screen Model	P1.53	P1.56	P1.875	P1.25
	Screen Resolution	1664*936 dots	1920*1080 dots	1920*1080 dots	3840*2160 dots
	Screen Size	2560mm(W)x1440mm(H)	3000mm(W)x1687mm(H)	3600mm(W)x2025mm(H)	4800mm(W)x2700mm(H)
	Module Size (Tile)	640*480	600*337.5	600*337.5	600*337.5
	Viewing Angle (H/ V)	120/120	120/120	120/120	120/120
	Brightness (cd/m2)	600 nits	600 nits	600 nits	600 nits
	Protection level	IP43	IP43	IP43	IP43
	Driver IC	CFD455A	CFD455A	CFD455A	CFD455A
	LED Encapsulation	Epistar copper wire	Epistar copper wire	Epistar copper wire	Epistar copper wire
	High Refresh Rate	3840 Hz	3840 Hz	3840 Hz	3840 Hz
	Scan Mothod	1/52 s	1/54 s	1/45 s	1/45 s

		115,6"	136"	163"	220"
Touch Sensor (NO Touch Option)	Type/ Points	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P
	Size	640*480	640*480	640*480	640*480
	Total Thickness	4 mm	4 mm	4 mm	4 mm
	Version	Lift and Foldable All-in-one			
	Special Treatment	GOB (On Demand)			
	Interface Type	USB			

Powe Supply	Working Voltage	AC100V~AC240V 50-60Hz			
	Max Power consumption	650 W/m2			
	Ave. Power consumption	200 W/m2			
	Total Power consumption	4KW (LED screen + Folding & lifting system + Media player)			
	Warranlty	2 Years (Panel 1 Year)			
	Certifications	CE - ROHS			

Control System	Screen Controller	Colorlight A200+4G/WiFi, and support 1 HDMI signal input			
	Interface Port	HDMI/ Wi-Fi/ USB/ 4G			
	Sending Box	A200+WiFi/4G			
	Receiving Card	MRV412			
	Operation System	Windows, Linux, Others			

Environmental	Temperature	-20°C +60°C			
	Humidity	+10 +90%			

Accessory	Included	Power Cable, Software Mobile Control, Flight case as base and cover, with brakes			
	Version	Lifting Range 1180mm(From ground to the bottom of the LED screen)			

		115,6"	136"	163"	220"
Type of packaging	Net Weight (Kg)	360 Kg (1Pcs)	391 Kg (1Pcs)	425 Kg (1Pcs)	452 Kg (1Pcs)
	Gross Weight (Kg)	462 Kg (1Pcs)	487 Kg (1Pcs)	504 Kg (1Pcs)	526 Kg (1Pcs)
	Net Item Size (L x W x H mm)	2560x48x1440	3004x50x1692	3604x50x2029	4893x53x2875
	Packing Size (L x W x H mm)	1660x96x1880	1890x96x2060	2030x96x2270	2110x96x2420

Remark	Other	Support Multiple Screen Loop Video Wall, LED screen folds into 3 parts: 640mm (L)/1280mm (M)/640mm (R)			

Note	The wide range of WTD LED Wall Solutions are technological mosaics composed of 2k / 4k led monitors with ultra-thin frames, effectively eliminating the annoying checkerboard effect and united and combined with each other they can achieve any desired size. Based on the characteristics of the environment in which they will be installed, World Trade Display is able to design and build self-supporting structures and push-pull hanging solutions capable of enhancing this type of maxi screens.

MONITOR TOUCH   OPEN FRAME TOUCH   MONITOR   OPEN FRAME   TOUCH SCREEN   TOUCH TABLE   FLOOR STANDING   KIOSK   VIDEOWALL

Display & Digital Signage Solutions

Elements & Spare Parts

Item	Description		Remark
LED Screen	Die-casting aluminium cabinet Indoor GOB LED module Various Cables Youyi Power supply		P1.53 indoor LED Size: 2.56x1.44m
	Spare parts		2 pcs 320x160mm GOB LED module
	Package		Flight case
Control system	Sending Card		A200+Wi-Fi/4G/HDMI
	Receiving Card		E320
	LED Software/App		LED Vision
Lifting & Folding	Lifting		2 buttons for lifting
	Folding		2 buttons for folding and unfolding
	Power distributor		

MONITOR TOUCH OPEN FRAME TOUCH MONITOR OPEN FRAME TOUCH SCREEN TOUCH TABLE FLOOR STANDING KIOSK VIDEOWALL

Display & Digital Signage Solutions