

MONITOR

CITY Series Wallmount Version



worldtradedisplay.com

Your choice to
discover the
technologies



Wide range
of innovative
digital products



Increase your
growth and
company profit



Panel Specification	Display Size (inch)	32	43	49	55
	Display Ratio	16:9	16:9	16:9	16:9
	Active Area (H x V)(mm)	706x400	947x535	1101x622	1215x686
	Viewing Angle (H/ V)	178°/ 178°	178°/178°	178°/ 178°	178°/ 178°
	Brightness (cd/m2)	500 Nits	500 Nits	500 Nits	500 Nits
	Contrast Ratio	5000:1	5000:1	5000:1	5000:1
	Display Resolution	3840*2160	3840*2160	3840*2160	3840*2160
Touch Sensor	Type/ Points	-	-	-	-
	Size	-	-	-	-
	Active Area (mm)	-	-	-	-
	Total Thickness	-	-	-	-
	Version/ Treatment	Indoor/ Tempered			
	Special Treatment	-			
	Interface Type	-			
	Compatible O/S	-			
Monitor Specification	Installation (VESA)	200x100	400x400	400x400	400x400
	Version/ Style	Wallmount			
	Interface	HDMI, (DVI)			
	Input Voltage	Max: 180 W/h - AC 100-240 V ~ (+/- 10%) 50/60 Hz			
	Media Player	Yes			
	Speaker	-			
	Warranty	2 Years			
	Certifications	CE - FCC - ROHS - Others on Demand			
PC System (Optional)	CPU	-			
	RAM	-			
	SSD	-			
	Network	-			
	System O.S.	-			
	Other Function	-			
Android (Optional)	O.S. Version	Android 9.0			
	Processor	Rockchip® RK3288 (1.5GHz, octa core)			
	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)			
	Media Resolutions	3840*2160			
	RAM	2 Gb			
	Flash	16 Gb EMMC			
	Ports	SD card socket, USB2.0*2, RJ-45*1, SD socket*1, HDMI*1,DC*1, Audio*1			
	LAN	10M/100M Ethernet			
	Wi-Fi	802.11 b/g/n Wi-Fi			
Environmental	Temperature (Consumer)	Consumer Panel: -5°C +45°C (Operating) / -20°C +60°C (Storage)			
	Temperature (Industrial)	Industrial Panel (Opt.): -25°C +75°C (Operating) / -45°C +85°C (Storage)			
	Humidity	+20% +80% (Operating) / +10 +90% (Storage)			
Accessory	Included	Power Cable, HDMI Cable, Wallmount Brackets			
	Others	-			
Type of packaging	Net Weight (Kg)	13,6 Kg (1Pcs)	18,7 Kg (1Pcs)	22,1 Kg (1Pcs)	29,6 Kg (1Pcs)
	Gross Weight (Kg)	15,1 Kg (1Pcs)	19,3 Kg (1Pcs)	29,2 Kg (1Pcs)	34,2 Kg (1Pcs)
	Net Item Size (L x W x H mm)	722x58x416	963x58x551	1117x58x638	1231x60x702
	Packing Size (L x W x H mm)	850x155x550	1085x140x695	1260x170x795	1430x210x890
Optional	Remark 1				
	Remark 2				
Note	World Trade Display designs and markets a very wide range of LCD/LED monitors in different sizes, from 7" up to 110" inches, always modern and elegant in shape. These screens are perfect for hanging on the wall or for installing on special self-supporting structures, ideal for exhibition stands, congresses, events or conferences. New WTD monitor designs are now a reality in the world of luxury hospitality.				



Display & Digital Signage Solutions

Panel Specification	Display Size (inch)	65	75	86	-
	Display Ratio	16:9	16:9	16:9	-
	Active Area (H x V)(mm)	1434x809	1653x932	1900x1071	-
	Viewing Angle (H/ V)	178°/178°	178°/ 178°	178°/ 178°	-
	Brightness (cd/m2)	500 Nits	500 Nits	500 Nits	-
	Contrast Ratio	5000:1	5000:1	5000:1	-
	Display Resolution	3840*2160	3840*2160	3840*2160	-
Touch Sensor	Type/ Points	-	-	-	-
	Size	-	-	-	-
	Active Area (mm)	-	-	-	-
	Total Thickness	-	-	-	-
	Version/ Treatment	Indoor/ Tempered			
	Special Treatment	-			
	Interface Type	-			
Compatible O/S	-				
Monitor Specification	Installation (VESA)	600x400	600x400	800x600	-
	Version/ Style	Wallmount			
	Interface	HDMI, (DVI)			
	Input Voltage	Max: 180 W/h - AC 100-240 V ~ (+/- 10%) 50/60 Hz			
	Media Player	Yes			
	Speaker	-			
	Warranty	2 Years			
Certifications	CE - FCC - ROHS - Others on Demand				
PC System (Optional)	CPU	-			
	RAM	-			
	SSD	-			
	Network	-			
	System O.S.	-			
	Other Function	-			
Android (Optional)	O.S. Version	Android 9.0			
	Processor	Rockchip® RK3288 (1.5GHz, octa core)			
	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)			
	Media Resolutions	3840*2160			
	RAM	2 Gb			
	Flash	16 Gb EMMC			
	Ports	SD card socket, USB2.0*2, RJ-45*1, SD socket*1, HDMI*1,DC*1, Audio*1			
	LAN	10M/100M Ethernet			
Wi-Fi	802.11 b/g/n Wi-Fi				
Environmental	Temperature (Consumer)	Consumer Panel: -5°C +45°C (Operating) / -20°C +60°C (Storage)			
	Temperature (Industrial)	Industrial Panel (Opt.): -25°C +75°C (Operating) / -45°C +85°C (Storage)			
	Humidity	+20% +80% (Operating) / +10 +90% (Storage)			
Accessory	Included	Power Cable, HDMI Cable, Wallmount Brackets			
	Others	-			
Type of packaging	Net Weight (Kg)	36.8 Kg (1 Pcs)	43.8 Kg (1 Pcs)	57.3 Kg (1 Pcs)	-
	Gross Weight (Kg)	38.4 Kg (1 Pcs)	48.2 Kg (1 Pcs)	64 Kg (1 Pcs)	-
	Net Item Size (L x W x H mm)	1450x60x825	1679x68x958	1926x67x1097	-
	Packing Size (L x W x H mm)	1630x175x945	1790x215x1073	2140x230x1214	-
Optional	Remark 1				
	Remark 2				
Note	World Trade Display designs and markets a very wide range of LCD/LED monitors in different sizes, from 7" up to 110" inches, always modern and elegant in shape. These screens are perfect for hanging on the wall or for installing on special self-supporting structures, ideal for exhibition stands, congresses, events or conferences. New WTD monitor designs are now a reality in the world of luxury hospitality.				



Display & Digital Signage Solutions

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World Trade Display it's a registered trademarks of World Trade Display Srl. All other trademarks are the property of their respective owners. Copyright World Trade Display Srl. All rights reserved.