



TOUCH MONITOR



MONITOR



OPEN FRAME



TOUCH SCREEN



DIGITAL SIGNAGE



TOUCH TABLE



FLOOR STANDING



VIDEO WALL

[www.worldtradedisplay.com](http://www.worldtradedisplay.com)

## MONITOR

### Monitor Solutions – MONOLITH Outdoor Wallmount Series



Display & Digital Signage Solutions

#### Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

#### All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

#### Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

#### Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Monitor
	Panel Size available	21.5"/ 43"/ 49"/ 55"/
	Active Area	21.5" 479 x 271 mm 16:9 1920 x 1080
	Aspect Ratio	43" 941 x 532 mm 16:9 1920 x 1080
	Resolution	49" 1074 x 604 mm 16:9 1920 x 1080
		55" 1214 x 684 mm 16:9 1920 x 1080
	Brightness	High
	Colors	16.7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	15/ 6 ms (Range)
	Contrast Ratio	1000:1/ 5000:1 (Range)
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	Input Frequency	Horizontal: 30 - 82 kHz Vertical: 60 - 75 Hz
	OSD	Remote Controller
	High Brightness	1000/ 2000 cd/m2 (Range)
High 4K Resolution	On Demand	
Double Display	No	
PC Functions	CPU	-
	RAM	-
	SSD	-
	Connections	-
	Media Player	No
	System OS	-
	Android	On Demand
	OPS Module Slot	-
	Other Function	-
Touch Functions	Technology	-
	Point	-
	Interface	-
	Surface Hardness	-
	Resolution	-
	Response Time	-
	Input Method	-
Connectivity	Interface	USB
	Speaker	2 x 5W Built in Stereo
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 60°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	400 x 400 Stand Mount
	Sheel Material	Alluminium Frame
	Glass	-
	Enclosure Color	Dark Gray Body and Handles Silver

FEATURES	REMARKS	SPECIFICATIONS
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	53W/ 65W (Range)
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko
Packaging	Dimension (Net) (L x W x H)	21.5" 650 x 440 x 223 mm 1 Pcs 19.1 Kg
	Weight (Single)	43" 1157 x 758 x 300 mm 1 Pcs 25.1 Kg
		49" 1290 x 830 x 300 mm 1 Pcs 27.5 Kg
	55" 1430 x 910 x 300 mm 1 Pcs 31.5 Kg	
	Carton Dimension	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	-
	Shell Material	Aluminium frame, tempered glass face & cold-rolled sheet body
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.