

OUTDOOR KIOSK DIGITAL SIGNAGE

Wall Mount Monitor Touch Screen SMAT Series
No Touch/ Player/ Android/ PC



worldtradedisplay.com

Your choice to discover the technologies



Wide range of innovative digital products



Increase your growth and company profit



Panel Specification	Display Size (inch)	32	43	49	55	65	75
	Display Ratio	16:9	16:9	16:9	16:9	16:9	16:9
	Active Area (H x V)(mm)	699x393	942x530	1074x604	1210x681	1429x804	1651x929
	Viewing Angle (H/ V)	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
	Brightness (cd/m2)	3000 Nits	3000 Nits	3000 Nits	3000 Nits	3000 Nits	3000 Nits
	Contrast Ratio	2000:1	4000:1	4000:1	4000:1	4000:1	4000:1
	Display Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080

Touch Sensor (NO Touch Optional)	Type/ Points	-	-	-	-	-	-
	Size	-	-	-	-	-	-
	Active Area (mm)	-	-	-	-	-	-
	Total Thickness	-	-	-	-	-	-
	Version	Outdoor					
	Special Treatment	IP65					
	Interface Type	USB					
Compatible O/S	Windows, Linux, Others						

Monitor Specification	Installation (VESA)	200x200	400x400	400x400	400x400	400x400	400x400
	Version/ Style	Outdoor Wallmount/ Antivandal/ Waterproof/ C.Fan System					
	Interface	Vga, HDMI					
	Input Voltage	Max: 240 W/h - AC 100-240 V ~ (+/- 10%) 50/60 Hz					
	Media Player	-					
	Speaker	2x5W, 8 Ohm					
	Warranty	2 Years (Panel 1 Year)					
	Certifications	CE - FCC - ROHS - Others on Demand					

PC System (Optional)	CPU	i3/ i5/ i7					
	RAM	4/ 8/ 16 Gb					
	SSD	64/ 128/ 256 Gb					
	Network	Wi-Fi, RJ45, VGA, HDMI 1.4, HDMI 2.0, 4xUSB 3.0					
	System O.S.	Windows 10 Trial					
	Other Function	-					

Android (Optional)	O.S. Version	Android 9.0 or higher version					
	Processor	Rockchip® 3288 (1.8GHz, Quad Core)					
	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)					
	Media Resolutions	1920*1080					
	RAM	2 Gb					
	Flash	8 Gb EMMC					
	USB	USB 2.0					
	LAN	10M/100M Ethernet					
Wi-Fi	802.11 b/g/n Wi-Fi						

Environmental	Temperature (Commercial)	Commercial Panel: 0°C +50°C (Operating) / -20°C +70°C (Storage)					
	Temperature (Industrial)	Industrial Panel (Opt.): -30°C +70°C (Operating) / -45°C +85°C (Storage)					
	Humidity	+20% +80% (Operating) / +10 +90% (Storage)					

Accessory	Included	Power Cable, Wallmount Brackets, Remote Control, Screw					
	Others	-					

Type of packaging	Net Weight (Kg)	33 Kg (1Pcs)	47 Kg (1Pcs)	56 Kg (1Pcs)	68 Kg (1Pcs)	79 Kg (1Pcs)	86 Kg (1Pcs)
	Gross Weight (Kg)	49 Kg (1Pcs)	54 Kg (1Pcs)	63 Kg (1Pcs)	76 Kg (1Pcs)	88 Kg (1Pcs)	94 Kg (1Pcs)
	Net Item Size (L x W x H mm)	778x144x473	1022x142x610	1154x142x684	1291x145x762	1509x145x884	1730x160x1008
	Packing Size (L x W x H mm)	1034x200x647	1115x230x732	1290x260x1040	1330x300x1120	1650x340x1330	1850x380x1420

Optional	Remark 1						
	Remark 2						

Note	World Trade Display designs and markets a very wide range of LCD/LED monitors in different sizes, from 7" up to 110" inches, always modern and elegant in shape. These screens are perfect for hanging on the wall or for installing on special self-supporting structures, ideal for exhibition stands, congresses, events or conferences. New WTD monitor designs are now a reality in the world of luxury hospitality.						
------	---	--	--	--	--	--	--



Display & Digital Signage Solutions