

OPEN FRAME TOUCH

BOND Series Optical Bonding Embedded Version



worldtradedisplay.com

Your choice to discover the technologies



Wide range of innovative digital products



Increase your growth and company profit



Panel Specification	Display Size (inch)	10.1	13.3	15.6	21.5	23.6
	Display Ratio	16:9	16:9	16:9	16:9	16:9
	Active Area (H x V) (mm)	217x136	294x165	387x236	479x270	525x297
	Viewing Angle (H/ V)	160°/160°	170°/170°	170°/160°	178°/178°	178°/178°
	Brightness (cd/m2)	1000 Nits	1000 Nits	1000 Nits	1000 Nits	1000 Nits
	Contrast Ratio	1000:1	1000:1	2000:1	2000:1	2000:1
	Display Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080

Touch Sensor	Type/ Points	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P
	Size	10.1"	13.3"	15.6"	21.5"	23.6"
	Active Area (mm)	217x136	294x165	387x236	479x270	525x297
	Total Thickness	5 mm	5 mm	5 mm	6 mm	6 mm
	Version/ Treatment	Outdoor/ Tempered, AntiVandal, AntiBrake				
	Special Treatment	A.R. Glass, Optical Bonding				
	Interface Type	USB, (RS232)				
	Compatible O/S	Windows, Linux, Others				

Monitor Specification	Installation (VESA)	100x75	100x75	100x75	100x75	100x75
	Version/ Style	Embedded Indoor				
	Interface	VGA, DVI, HDMI				
	Input Voltage	Max: 40 W/h - AC 100-240 V ~ (+/- 10%) 50/60 Hz				
	Media Player	-				
	Speaker	-				
	Warranty	2 Years				
	Certifications	CE - FCC - ROHS - Others on Demand				

PC System	CPU	-
	RAM	-
	SSD	-
	Network	-
	System O.S.	-
	Other Function	-

Android	O.S. Version	-
	Processor	-
	Media Formats	-
	Media Resolutions	-
	RAM	-
	Flash	-
	USB	-
	LAN	-
Wi-Fi	-	

Environmental	Temperature (Commercial)	Commercial Panel: 0°C +50°C (Operating) / -20°C +70°C (Storage)
	Temperature (Industrial)	Industrial Panel (Opt.): -30°C +70°C (Operating) / -45°C +85°C (Storage)
	Humidity	+20% +80% (Operating) / +10 +90% (Storage)

Accessory	Included	Power Cable, Wallmount Brackets
	Others	Light Sensor

Type of packaging	Net Weight (Kg)	1.6 Kg (1Pcs)	3 Kg (1Pcs)	4.4 Kg (1Pcs)	5.2 Kg (1Pcs)	6.3 Kg (1Pcs)
	Gross Weight (Kg)	2.3 Kg (1Pcs)	3.6 Kg (1Pcs)	5 Kg (1Pcs)	10.8 Kg (2Pcs)	6.7 Kg (1Pcs)
	Net Item Size (L x W x H mm)	287x42x206	387x40x259	422x40x286	554x48x349	645x53x417
	Packing Size (L x W x H mm)	460x135x405	460x140x340	460x140x340	610x230x410	660x135x455

Optional	Remark 1	
	Remark 2	

Note	The latest technology in terms of outdoor solutions is marketed by WTD with the new series of open frame touch screen called BOND; completely vacuum panel and touch sensor with no air between the two parts, absolutely improving readability in sunlight and increasing reliability in extreme conditions, definitely eliminating the problem of black screen in the sun.
------	--



Display & Digital Signage Solutions

Panel Specification	Display Size (inch)	27	32	43	49	55
	Display Ratio	16:9	16:9	16:9	16:9	16:9
	Active Area (H x V) (mm)	652x393	765x460	997x590	1074x603	1210x680
	Viewing Angle (H/ V)	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
	Brightness (cd/m2)	1000 Nits	1000 Nits	1000 Nits	1000 Nits	1000 Nits
	Contrast Ratio	2000:1	2000:1	2000:1	2000:1	2000:1
	Display Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080
Touch Sensor	Type/ Points	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P
	Size	27"	32"	43"	49"	55"
	Active Area (mm)	652x393	765x460	997x590	1074x603	1210x680
	Total Thickness	6 mm	6 mm	6 mm	6 mm	6 mm
	Version/ Treatment	Outdoor/ Tempered, AntiVandal, AntiBrake				
	Special Treatment	A.R. Glass, Optical Bonding				
	Interface Type	USB, (RS232)				
Compatible O/S	Windows, Linux, Others					
Monitor Specification	Installation (VESA)	100x75	200x400	400x400	400x400	600x400
	Version/ Style	Embedded Indoor				
	Interface	VGA, DVI, HDMI				
	Input Voltage	Max: 110 W/h - AC 100-240 V ~ (+/- 10%) 50/60 Hz				
	Media Player	-				
	Speaker	-				
	Warranty	2 Years				
	Certifications	CE - FCC - ROHS - Others on Demand				
PC System	CPU	-				
	RAM	-				
	SSD	-				
	Network	-				
	System O.S.	-				
	Other Function	-				
Android	O.S. Version	-				
	Processor	-				
	Media Formats	-				
	Media Resolutions	-				
	RAM	-				
	Flash	-				
	USB	-				
	LAN	-				
Wi-Fi	-					
Environmental	Temperature (Commercial)	Commercial Panel: 0°C +50°C (Operating) / -20°C +70°C (Storage)				
	Temperature (Industrial)	Industrial Panel (Opt.): -30°C +70°C (Operating) / -45°C +85°C (Storage)				
	Humidity	+20% +80% (Operating) / +10 +90% (Storage)				
Accessory	Included	Power Cable, Wallmount Brackets				
	Others	Light Sensor				
Type of packaging	Net Weight (Kg)	7.1 Kg (1Pcs)	13.5 Kg (1Pcs)	18.7 Kg (1Pcs)	26 Kg (1Pcs)	30 Kg (1Pcs)
	Gross Weight (Kg)	7.6 Kg (1Pcs)	14 Kg (1Pcs)	19.3 Kg (1Pcs)	39 Kg (1Pcs)	48 Kg (1Pcs)
	Net Item Size (L x W x H mm)	692x55x430	804x79x499	1095x76x683	1223x78x754	1295x64x774
	Packing Size (L x W x H mm)	785x185x515	875x185x590	1140x205x630	1220x140x760	1375x140x840
Optional	Remark 1					
	Remark 2					
Note	The latest technology in terms of outdoor solutions is marketed by WTD with the new series of open frame touch screen called BOND; completely vacuum panel and touch sensor with no air between the two parts, absolutely improving readability in sunlight and increasing reliability in extreme conditions, definitely eliminating the problem of black screen in the sun.					



Display & Digital Signage Solutions

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World Trade Display it's a registered trademarks of World Trade Display Srl. All other trademarks are the property of their respective owners. Copyright World Trade Display Srl. All rights reserved.