



TOUCH MONITOR



MONITOR



OPEN FRAME



TOUCH SCREEN



DIGITAL SIGNAGE



TOUCH TABLE



FLOOR STANDING



VIDEOWALL

www.worldtradedisplay.com

TOUCH MONITOR

I.R. Touch Monitor Solutions - INDY Wallmount Series



Display & Digital Signage Solutions

Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative & communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Touch Monitor
	Panel Size available	32" / 42" / 50"
	Active Area	32" 698 x 393 mm 16:9 1920 x 1080
	Aspect Ratio	42" 930 x 524 mm 16:9 1920 x 1080
	Resolution	50" 1096 x 616 mm 16:9 1920 x 1080
	Brightness	300/ 400 cd/m2 (Range)
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	14/ 6,5 ms (Range)
	Contrast Ratio	1300:1/ 5000:1 (Range)
	Input Video Format	RGB Analog/ DVI-D
	Input Video Signal	VGA/ HDMI
	Input Frequency	Horizontal: 30 - 82 kHz Vertical: 60 - 75 Hz
	OSD	Ctrl(back):Menu,Ch+,Ch-Vol+,Vol-,Source,Standby
	High 4K Resolution	On Demand
High Brightness	On Demand	
Double Display	No	
PC Functions	CPU	-
	RAM	-
	SSD	-
	Connections	-
	Media Player	-
	System OS	-
	Android	-
	OPS Module Slot	32": No - 42" / 50": Yes
	Other Function	-
Touch Functions	Technology	Infrared Touch (IR)
	Point	Max: 6 Point
	Interface	USB (B Type)
	Surface Hardness	-
	Resolution	32768 x 32768
	Response Time	< 5 ms
	Input Method	Finger or any pointer minimum radius 3 mm
Connectivity	Interface	USB (B Type), VGA, HDMI
	Speaker	5 W x 2 Channels
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 60°C
	Transmittance	> 89%
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	32": 200 x 100 mm - 42" / 50": 400 x 400 mm Stand Mount
	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	-
	Enclosure Color	Black
	Stand	Available in Different Style
	Mounting (Option)	-

FEATURES	REMARKS	SPECIFICATIONS
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	LED: 65/ 140W (Range)
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko
Packaging	Dimension (Net) (L x W x H) Weight (Single)	32" 767 x 63 x 462 mm 17 Kg 42" 1001 x 65 x 594 mm 28 Kg 50" 1162 x 67 x 683 mm 29 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also from 6 to 32 MultiPoint's
		Available also in PCAP Technology Version
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.