

www.worldtradedisplay.com

TOUCH MONITOR

PCAP Touch Monitor Solutions - JEN Integrated Series



Wide Range, Easy & Accurate

Display & Digital Signage Solutions

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

f 🞯 in 🕩

marketing@worldtradedisplay.com



TECHNICAL SPECIFICATION

TOUCH MONITOR | PCAP

JEN SERIES

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Touch Monitor
	Panel Size available	21,5"
	Active Area Aspect Ratio Resolution	21,5" 478 x 269 mm 16:9 1920 x 1080
	Brightness	250 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 170° Vertical (up/down): 160°
	Response Time (Pixel)	5 ms
	Contrast Ratio	1000:1
	Input Video Format	RGB Analog/ HDMI
	Input Video Signal	VGA/ HDMI
	High 4K Resolution	On Demand
	High Brightness	On Demand
	Double Display	Νο
PC Functions	СРИ	-
	RAM	
	SSD	
	Connections	
	Media Player	
	System OS	
	Android	-
	OPS Module Slot	-
	Other Function	
Touch Functions	Technology	РСАР
	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<15
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	-
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 40°C Storage: -20° ~ 65°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	75 x75 Side/ 75 x 100 Side/ 100 x 100 Side/
	Sheel Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Silver Frame and Black Body
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	Max: 20W
	Cables	Power Supply with Cable Schuko
	Input Connector	AC: Cable Power Schuko



TECHNICAL SPECIFICATION

TOUCH MONITOR | PCAP

JEN SERIES

FEATURES	REMARKS	SPECIFICATIONS
Packaging	Dimension (Net) (L x W x H) Weight (Single)	21.5″ 534 x 36 x 321 mm 3.6 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World Trade Display it's a registered trademarks of World Trade Display Srl. All other trademarks are the property of their respective owners. Copyright World Trade Display Srl. All rights reserved.