



- NOTES**
1. ALL DIMENSION ARE IN MILLIM
  2. TRANSDUCERS ARE LOCATED 7 POSITIONS SHOWN, GLASS IS BE UNDER THE TRANSDUCERS.
  3. CABLE ROUTING ADDS A MAXII 4.0mm TO INDICATED SECTION OF 4. 8X19 HOUSING MATES WITH CONTROLLER.
  5. REFLECTIONAL ARRAY AND 2 TRANSDUCER ON THE FRONT OF 6. CABLE CLIP, MATERIAL: META 7. GLASS BOARD.
  8. CABLE, OUTER LAYER MATERI
  9. THE TOUCH ACTIVE AREA IS LE VIEWABLE AREA TO FACILITATE

External Dimensions	512*304*4
Display Area	484*276
Active Area	476*268
Thickness	4
Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
WaterPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
Safety	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>

CONNECTION CHART		INSULATION COLOR OVERALL SHIELD	
PIN	SIGNAL		
1	GND		
2	KEY		
3	Y-in2	BLUE	
4	Y-out	BLUE	
5	Y-in1	BLACK	
6	GND	YELLOW	
7	GND		
8	GND		
9	X-in2		
10	X-out		
11	X-in1		
12	KEY		